



**chemlube**  
INTERNATIONAL LLC

## PRODUCT DATA SHEET

Code 30001

### Chemlube Universal Tractor Fluid

Chemlube Universal Tractor Fluid is formulated as a multi-purpose high quality fluid for use in hydraulic, final drive, wet brake, transmission differential, and power steering systems commonly used in farm tractors and other off road equipment. This product meets the performance requirements of all major brands of tractors and farm equipment, providing excellent wear protection, seal compatibility, corrosion protection, gear pitting protection and proper operation of wet brakes and clutches.

#### Performance Profile:

- Ford M2C86B,C
- Ford M2C134D
- John Deere J20C, J20D
- Komatsu KES 07.866, AXO80
- Volvo WB 101 (VCE 97303)
- API GL-4

#### TYPICAL PROPERTIES

| <i>Test</i>         | <i>Method</i> | <i>Results</i> |
|---------------------|---------------|----------------|
| Viscosity 100°C cSt | ASTM D445     | 9.3            |
| Viscosity 40°C cSt  | ASTM D445     | 58.3           |
| Viscosity Index     | ASTM D2270    | 140            |
| Flash Point, °C     | ASTM D92      | 215            |
| Pour Point, °C      | ASTM D97      | -38            |
| Calcium, ppm        | Spectrometer  | 1700           |
| Zinc, ppm           | Spectrometer  | 725            |

**NOTE:** Values are typical only. Due to ongoing research, development and product improvement, product formulas are subject to change without notice. Chemlube International cannot know all the uses and conditions to which this product may be subjected, therefore it is the user's responsibility to ascertain that it is suitable for any intended use or application.

Reviewed/ Revised 4-14-20

**Contact: Chemlube International LLC**, 500 Mamaroneck Avenue, Harrison, NY 10528 USA  
Tel: +1-914-381-5800; fax: +1-914-381-8988 E -mail: info@chemlube.com., www.chemlube.com