



chemlube
INTERNATIONAL LLC

PRODUCT DATA SHEET

Code 30001

Chemlube Universal Tractor Fluid

Chemlube Universal Tractor Fluid is formulated as a multi-purpose high quality fluid for use in hydraulic, final drive, wet brake, transmission differential, and power steering systems commonly used in farm tractors and other off road equipment. This product meets the performance requirements of all major brands of tractors and farm equipment, providing excellent wear protection, seal compatibility, corrosion protection, gear pitting protection and proper operation of wet brakes and clutches.

Performance Profile:

- AGCO: Massey Ferguson M-1145, M-1143, M-1141, M-1138, M-1135 Permatran III, White Q-1826
- Allison C-4 as part of JD20C
- API GL-4
- Case New Holland MAT 3505
- Case New Holland and MAT 3525&3526, ESN M2C86B
- Eaton Vickers (Mobil hydraulic systems according to brochure 694 using procedure ATS-373 with 35 VQ25 pump)
- JCMAS HK P-041 & P-042
- John Deere J-20C/D
- Komatsu
- Kubota UDT
- Parker (Dennison UTTO, HF-0 through 02) in Group I Base oil
- Volvo (VCE 1273.03 and WB101)

Test	TYPICAL PROPERTIES	
	Method	Results
Viscosity 100°C cSt	ASTM D445	9.5
Viscosity 40°C cSt	ASTM D445	53.4
Viscosity Index	ASTM D2270	160
Flash Point, °C	ASTM D92	215
Pour Point, °C	ASTM D97	-38
Calcium, ppm	Spectrometer	3150
Zinc, ppm	Spectrometer	1300

NOTE: Values are typical only. Due to ongoing research, development and product improvement, product formulas are subject to change without notice. Chemlube International cannot know all the uses and conditions to which this product may be subjected, therefore it is the user's responsibility to ascertain that it is suitable for any intended use or application.

Contact: Chemlube International LLC, 500 Mamaroneck Avenue, Harrison, NY 10528 USA
Tel: +1-914-381-5800; fax: +1-914-381-8988 E-mail: info@chemlube.com., www.chemlube.com