



Chemlube Universal Tractor Fluid

Chemlube Universal Tractor Fluid is formulated as a multi-purpose high quality fluid for use in hydraulic, final drive, wet brake, transmission differential, and power steering systems commonly used in farm tractors and other off road equipment.

It meets the performance requirements of all major brands of tractors and farm equipment, providing excellent wear protection, seal compatibility, corrosion protection, gear pitting protection and proper operation of wet brakes and clutches.

APPLICATIONS:

Manufacturer

Allis Chalmers
Allison (DDC)
Caterpillar
John Deere
Deutz Allis
Ford New Holland
International Harvester
J.I. Case

KUBOTA
Massey-Ferguson
Oliver
White Farm Equipment

Specification

S25743, PF 821
C3, C4
Power Shift transmission specifying Cat TO2
J20C, J20B, HyGard J14B/C, type 303, Quatrol
HTF(PF821), 821XL
M2C134-A/B/C/D, M2C86-B/C, M2C53-A, M2C41-B
B-6 (HY-TRAN)
MS-1209 (HY-TRAN ULTRA), MS-1210 (HY-TRAN PLUS)
MS-1204, MS-1205, MS-1206, MS-1210 (TCH), AND B-6, TFD
Universal Transhydraulic Fluid (UTD)
M1110, M1127 A/B, M1135, M1141 (Permatran III)
Type 55
Q1766B, Q1826, Q1802, Q1705, Q1722

TYPICAL PROPERTIES

Viscosity @100C cSt	9.4
Viscosity @ 40C cSt	56.0
Viscosity Index	140
Pour Point, C	-38
Flash Point, C/F	215/430
Color (ASTM)	3.0

NOTE: Values are typical only. Due to ongoing research, development and product improvement, product formulas are subject to change without notice. Chemlube International can not know all the uses this product may be subject to so it is the user's responsibility to ascertain that it is suitable for an intended use or application.

Contact: Chemlube International
500 Mamaroneck Avenue
Harrison, NY 10528 USA
Tel: +1-914-381-5800; fax: +1-914-381-8988
E-mail: info@chemlube.com
www.chemlube.com

PUTF 6-2005